

# Warranty certificate

D-MAX Belgium ensures that MAX PRO 34 Ultra-Seal can be safely used for seams and joints to seal all natural stone surfaces if the instructions and notes listed below are carefully monitored and observed.

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name:</b>   | <b>MAX PRO 34 Ultra-Seal</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Product code:</b>   | <b>S-2000 - Transparant - 310 ml</b><br><b>S-2001 - White - 310 ml</b><br><b>S-2002 - Grey - 310 ml</b><br><b>S-2003 - Anthracite- 310 ml</b>                                                                                                                                                                                                                                                                                                                                        |
| <b>Applications:</b>   | Sealing joints between natural stone and natural stone, natural stone and non-porous substrates, natural stone and porous surfaces.                                                                                                                                                                                                                                                                                                                                                  |
| <b>Processing:</b>     | Surface should be dry, clean, grease-free and free of any loose parts, glue, old silicone and / or other residus of seal joints, cleaning products, ...<br>Degrease the joints that need to be sealed with pH-neutral cleaner and let evaporate.<br>Apply in a single motion and in an angle of 45 ° and if necessary, fill the joint with backing material so the joint can work. Finished seams with pH-neutral soap solution and clean the seams with alcohol diluted with water. |
| <b>Exceptions:</b>     | Avoid applying of the sealant in a too thin layer. In these places, it is possible that the sealant is not optimal curing and adhering. Soapy water / Finisher can leave stains on porous surfaces. Rinse with lukewarm water immediately after finishing sealant joints is recommended.                                                                                                                                                                                             |
| <b>Miscellaneous:</b>  | In order to prevent discoloration and yellowing of the joint must be applied in a neutral environment. avoiding the presence, during curing of all possible acids, cigarette smoke, acetic acid-containing silicones, chlorine or chlorine fumes.<br>The alkaline environment is not suitable for using MAX PRO 34 Ultra-Seal.<br>In the absence of daylight the kit can yellowing.<br>Not suitable for bitumen, PE PTFE, PP, PC and PMMA.                                           |
| <b>Disclaimer</b>      | D-MAX Belgium guarantees that its products are conform to its technical data sheets and can be used by the professional for all the applications described herein. For professional use only.<br>D-MAX Belgium is not liable for applications where the good workmanship is not followed and / or poorly finished joints.                                                                                                                                                            |
| <b>Technical data:</b> | Product specifications and the DoP can be viewed or downloaded from our website :<br><a href="http://www.d-max.eu">www.d-max.eu</a> .                                                                                                                                                                                                                                                                                                                                                |